

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

1. - 15. (Canceled).

16. (Currently Amended) A computer-readable storage device containing instructions for controlling a data processing system to perform a method for supplying data to a view presenting a model, the view having at least one user interface (UI) element and relating to a controller for manipulating the model, the method comprising:

creating a run-time context data structure, the run-time context data structure being based on a design-time context data structure, the design-time context data structure including a context structure element that is bound to the UI element;

storing the run-time context data structure in a storage area that relates to the controller; and

using a supply function to provide content for the run-time context data structure.

17. (Currently Amended) A computer-readable storage device containing instructions for controlling a data processing system to perform a method for accessing application data by an application using a model of the application and at least one controller for manipulating the model, the method comprising:

providing a storage area ~~that relates to the controller~~, the storage area being organized according to a design-time context data structure having declared

relationships between the application data, the design-time context data structure relating to the controller; and

storing a run-time context data structure that is based on the design-time context data structure;

accessing a structure element of the run-time context data structure, the context structure element comprising a node collection;

evaluating the node collection; and

if the result of evaluating the node collection requires filling at least one element of the node collection:

sending a query to a computer system; and

in response to the query, receiving from the computer system at least one data instance that is used to fill the at least one element of the node collection.

18. (Currently Amended) A computer-readable storage device containing instructions for controlling a data processing system to perform a method, the method comprising:

establishing a model, the model implementing application logic of an application;

establishing at least one view for presenting the model, the view comprising a user interface (UI) element which is bound to a first context data structure;

establishing at least one controller for manipulating the model, the at least one controller relating to the at least one view; and

establishing at least one storage area, ~~the at least one storage area relating to the at least one controller and~~ for storing an instance of the first context data structure,

the instance of the first context data structure comprising data having been stored in the storage area by an access method associated with the at least one controller, the first context data structure having been declared prior to execution of the application, the first context data structure relating to the at least one controller.

19. (Currently Amended) The computer-readable storage device of claim 18, wherein the instance of the first context data structure comprises one or more node elements, each node element comprising one or more data fields based on the first context data structure.

20. (Previously Presented) The computer-readable storage device of claim 19, wherein one or more of the node elements are grouped into a node collection.

21. (Previously Presented) The computer-readable storage device of claim 20, wherein one or more of the node elements in the node collection are grouped into a node selection.

22. (Previously Presented) The computer-readable storage device of claim 21, wherein one of the node elements in the node selection is identified as a lead selection element.

23. (Previously Presented) The computer-readable storage device of claim 22, wherein the UI element displays data from the lead selection element.

24. (Currently Amended) The computer-readable storage device of claim 18, wherein the access method is part of an application programming interface (API) for accessing the instance of the first context data structure.

25. (Currently Amended) The computer-readable storage device of claim 18, wherein the method further comprises:

establishing an instance of a second context data structure, the second context data structure having been declared to be a child of the first context data structure prior to execution of the application.

26. (Currently Amended) The computer-readable storage device of claim 25, wherein the instance of the first context data structure comprises one or more node elements of a first type grouped into a first node collection, and the instance of the second context data structure comprises one or more node elements of a second type grouped into a second node collection.

27. (Previously Presented) The computer-readable storage device of claim 26, wherein one of the node elements in the first node collection is identified as a selected element, and wherein the node elements in the second node collection depend on the selected element.

28. (Previously Presented) The computer-readable storage device of claim 26, wherein the second node collection has a state.

29. (Previously Presented) The computer-readable storage device of claim 28, wherein the state is selected from the group of valid, invalid, and unfilled.

30. (Previously Presented) The computer-readable storage device of claim 29, wherein the method further comprises:

establishing a supply function for determining a content of the one or more node elements in the second node collection if the state of the second node collection is invalid or unfilled.

31. (Previously Presented) The computer-readable storage device of claim 30, wherein the supply function is implemented as a method of the at least one controller.